

Samsung Smart Signage QMR-A series

Display any content in ultra-high definition with incredibly rich color on slim, efficient signage

Through intelligent UHD upscaling technology, Samsung's QMR-A series performs edge restoration and noise reduction to deliver UHD picture quality even with lower resolution content. As an added benefit, this series also features reliable, non-glare panels that provide better visibility from all angles. Backed by Tizen 4.0, this series provides reinforced capability with multiple web formats and secured protection. Additionally, its new slim design simplifies wall mounting and ensures seamless installation.


Highlights

- Engage customers with lifelike images through ultra high-definition resolution
- Deliver UHD-level picture quality even with lower resolution content through Crystal Processor 4K supporting advanced UHD upscaling technology
- Dynamic Crystal Display allows viewers to enjoy a wider spectrum of colors, up to one billion shades
- Symmetrical, slim design simplifies installation and complements any environment
- Secure, PC-free operation through Knox and rigid three-layer protection
- Reliable, non-glare panels provide better visibility from all angles, anytime of day allowing businesses to deliver accurate information 24/7




Industry trend

With visual display technology continually improving, viewers have developed an ever-growing expectation for better – and bigger – picture quality. Users, more than ever, want to captivate customers with truly lifelike images and gain a competitive edge over their industry peers with best-in-class displays. This is reflected in the fact that UHD resolution continues to grow in popularity, becoming an essential way for brands to impress customers amid a wider variety of stunning, aesthetical visuals and content. This trend is coupled with demand for larger screen sizes, particularly in the 75-inch and above category, enabling businesses to differentiate themselves and display content in a more impactful way than ever before.



Demand for bigger screens is on the rise **



*,** Source : Omdia, Public Displays Market Tracker Q1 2020, July 2020. Revenues in USD Millions. Does Not Include Consumer TVs Used as Public Displays. Not an Endorsement of Samsung Electronics Co. Ltd. Any Reliance on these results is at the third-party's own risk.

Why Samsung's QMR-A series?

Samsung's superior visual display technology has positioned them as the industry leader in the digital signage market for a decade* and Samsung brand having been No.1 in sales for 12 consecutive years in the display market**. As an expert in picture quality in the display industry, Samsung is able to deliver best-in-class picture quality through their QMR-A series. The signage provides rich and flawless colors, sleek and durable design, powerful performance through SSSP 6 and secured protection. Samsung's QMR-A series is also able to upscale the low resolution content to UHD picture quality. For commercial displays, this technology advancement means highly visible signage with unmatched accuracy to help capture the attention of potential customers. It also means savings both in cost and time for businesses who can produce content more inexpensively at a lower resolution and still display it in stunning UHD quality.

* Results based on Omdialformer IHS) report "Public Displays Market Tracker", 2009 – 2018. Information is not an endorsement of Samsung. Any reliance on these results is at the third party's own risk. ** According to market research company "Omdia". Ranking in terms of shipments. Results are not an endorsement of Samsung. Any reliance on these results is at the third-party's own risk.









Key features




Incredible 4K picture quality

Samsung's new QMR-A series is able to capture customer attention by providing an incredibly clear picture, showcasing lifelike images and intricate details better than ever before thanks to ultra high-definition 4K resolution.



Perfect view with non-glare display

When clear visibility is essential, the QMR-A series incorporates key features including up to 500 nit brightness and reliable, non-glare panels that provide better visibility from all angles, anytime of day. The display is ideal for locations such as airports and commuter stations where 24/7 access to clear and accurate information is crucial.



Crystal Processor 4K

Samsung's global leadership in display technology and picture quality spans more than a decade. Thanks to superior semi-conductor technology, Samsung has developed the powerful video processor available. Additionally, intelligent UHD upscaling technology is a cutting-edge solution based on Samsung's proprietary UHD Processor that allows content developed at a lower resolution to be elevated to UHD-level quality. It also performs edge restoration and noise reduction to optimize on-screen text and imagery with crisp edges and fine detail.



Dynamic Crystal Display

Dynamic Crystal Display is what brings the incredible, lifelike color to Samsung displays. Using 10-bit processing, the displays are able to showcase a wider spectrum of colors — up to a billion different shades — capturing subtle differences for flawless color expression, critical to businesses in ensuring brand consistency across communication channels. The QMR-A series also features HDR+ functionality that converts standard definition (SDR) content to HDR quality for sharper contrast and more vivid colors.

Key features



Slim and symmetrical design

The all-new slim and symmetrical design of the QMR-A series significantly simplifies wall mounting the display and ensures installation is a seamless process. The display's power inlet direction has been redesigned to sit flush against the wall. The new design sets guarantees a long life cycle ensuring the QMR-A series will stand the test of time.



Samsung Workspace secured by Knox

Samsung Workspace is a powerful new feature fortified by proprietary Knox security technology allowing users to create an enhanced virtual collaboration workspace without needing a PC in the room, or any physical connection. Simply connect a keyboard and mouse to the display and immediately get to work accessing a PC remotely or web based cloud services such as Microsoft Office 365 and VMWare Horizon.

* Samsung Workspace feature support may vary by region and market conditions.
* The scheduled availability of this feature varies by model.



Wi-Fi and Bluetooth built-in

The QMR-A series features a nearly endless range of business use cases thanks to built-in Wi-Fi and Bluetooth. Wireless connectivity allows for personalized and interactive services including enabling integration with beacon technology in store, while also simplifying how businesses showcase content.

* Image is for illustrative purposes only, specific application or program may have to be developed for the depicted usage scenario.



Clean cable management

In a corporate or retail environment, the back of a display is often visible to customers. With the QMR-A series' new cable guide feature retailers can tuck messy cables away from view. This allows for a clean and more visually-appealing customer shopping experience.



Powerful, all-in-one solution

The Samsung Smart Signage Platform (SSSP) is an open-source, all-in-one solution embedded in Samsung Smart signage that simplifies installation and maintenance. With SSSP, there is no need for any external devices to communicate with the server or play digital media enjoying easy development, reinforced capability with multiple web formats, and secured protection.



Industry standard certified

QMR-A displays are EMC class B compliant, providing a safe and healthy viewing environment by meeting strict standards of electromagnetic wave emission and assuring reliable operation even near other electronic equipment. The displays are also registered by EPEAT, the global ecolabel for IT, confirming the hardware is sustainable for the full product lifecycle, from design and production to energy use and recycling.

Specifications

	Model		QM32R-A	QM43R-A	QM50R-A
	Diagonal Size	Class	32	43	50
	Diagonal Size	Measured	31.5	42.5	49.5
	Туре		Edge LED BLU	Edge LED BLU	Edge LED BLU
	Resolution		FHD (1920 x1080)	UHD (3840 x 2160)	UHD (3840 x 2160)
	Pixel Pitch (mm)		0.360(H) x0.360(V)	0.2451(H) x 0.2451(V)	0.279(H) x 0.279(V)
	Active Display Area		698.4(H) x 392.85(V)	941.184 (H) x 529.416 (V)	1073.78(H) x 604.00(V)
	Brightness(Typ.)		400	500	500
Panel	Contrast Ratio (Typ.)		5000:1	4000:1	4000:1
	Viewing Angle(H/V)		178/178	178/178	178/178
	Response Time (G to (5)	8ms(Typ.)	8ms(Typ.)	8ms(Typ.)
			16.7M(True Display)	16.7M(True Display)	16.7M(True Display)
	Display Colors		1.07B(Ditherd10bit)	1.07B(Ditherd10bit)	1.07B(Ditherd10bit)
	Color Gamut Operation Hour		72%	92% (DCI-P3, CIE1976)	92% (DCI-P3, CIE1976)
			24/7	24/7	24/7
	Haze		2%	44%	25%
	Dynamic C/R		MEGA	MEGA	MEGA
	H-Scanning Frequency V-Scanning Frequency Maximum Pixel Frequency Speaker Type		30 ~ 81kHZ	30 ~ 81kHZ	30 ~ 81kHZ
Display			48~75HZ	48~75HZ	48~75HZ
			594MHz	594MHz	594MHz
Sound			Built in Speaker(10W +10W)	Built in Speaker(10W +10W)	Built in Speaker(10W +10W)
Journa	Speakertype	RGB			Display Port 1.2 (1)
			Display Port 1.2 (1)	Display Port 1.2 (1)	
	INDUT	VIDEO	HDMI 2.0 (2)	HDMI2.0 (2)	HDMI 2.0 (2)
	INPUT	HDCP	HDCP2.2	HDCP2.2	HDCP2.2
		AUDIO	Stereo Mini Jack, HDMI/Audio(Common)	Stereo Mini Jack, HDMI/Audio(Common)	Stereo Mini Jack, HDMI/Audio(Common)
		USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2
		RGB	N/A	N/A	N/A
onnectivity		VIDEO	N/A	N/A	N/A
	OUTPUT	AUDIO	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
		Power Out	N/A	N/A	N/A
		USB	N/A	N/A	N/A
	EXTERNAL CONTROL		RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45	RS232C(in/out) thru stereo jack, RJ45
	EXTERNAL SENSOR		IR	IR	IR
	Tuner		N/A	N/A	N/A
	Туре		Internal	Internal	Internal
	Power Supply	N. D	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz
	PowerConsumption	Max[W/h]	72	110	170.5
Power		Typical[W/h]	44	74	117
		Rating[W/h]	65	100	155
		BTU(Max)	245.7	375.1	581.4
		Sleep mode	0.5	0.5	0.5
		Off mode	N/A	N/A	N/A
Mechanical	Dimension(mm)	Set	725.1 x 419.6 x 34.6	967.5 x 557.7 x 48.3	1099.2 x 631.5 x 46.3
	Dimension(mm)	Package	812 x 513 x 120	1095 x 676 x 151	1247 x 772 x 152
		Set	5.7	10	13.5
	Weight (kg)	Package	8	13.3	18
Spec	VESA Mount		200 X 200	200 X 200	200 X 200
	Protection Glass		N/A	N/A	N/A
	Stand Type		Foot Stand (Optional)	Foot Stand (Optional)	Foot Stand (Optional)
	Bezel Width (Top/Side/Bot) (mm)		8.8mm(U/L/R/B)	9.2mm(U/L/R), 11.2mm(B)	9.2mm(U/L/R), 11.2mm(B)
	Operating Temperature		0°C~ 40°C	0°C~ 40°C	0°C~ 40°C
Operation	Humidity		10~80%	10~80%	10~80%
	Key Orientation		FHD Signage Display Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0	UHD Signage Display Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0	UHD Signage Display Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0
			Landscape / Portrait	Landscape / Portrait	Landscape / Portrait
	H/W		Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker(10W 2ch),	Temperature Sensor,Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker(10W 2ch),	Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker(10W 2ch),
	Special	S/W	IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option,	Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option,	IPSx Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option,
			Plug&Play (Initial Setting)	Plug&Play (Initial Setting)	Plug&Play (Initial Setting)
		Processor	Cortex A721.7GHz Quad-Core CPU	Cortex A721.7GHz Quad-Core CPU	Cortex A721.7GHz Quad-Core CPU
	Internal Player (Embedded H/W)	On-Chip Cache	L1 Instruction Cache : 48KB	L1 Instruction Cache : 48KB	L1 Instruction Cache : 48KB
Feature		Memory	L1 Data Cache : 32KB L2 Cache : 2MB	L1 Data Cache : 32KB L2 Cache : 2MB	L1 Data Cache : 32KB L2 Cache : 2MB
		Clock Speed	1.7GHz	1.7GHz	1.7GHz
		Main Memory	2.5GB	2.5GB	2.5GB
		Interface	LPDDR41.5GHz 64bit	LPDDR41.5GHz 64bit	LPDDR41.5GHz 64bit
		Graphics	Graphic resolution : 1920x1080 Output resolution : 1920x1080 (Scale up from graphic processing result.)	Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)	Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)
		Storage (FDM)	(Scale up from graphic processing result.) 8GB (3.88GB Occupied by O/S, 4.12GB Available)	(Scale up from graphic processing result.) 8GB (3.88GB Occupied by O/S, 4.12GB Available)	(Scale up from graphic processing result.) 8GB (3.88GB Occupied by O/S, 4.12GB Available)
		Multimedia	*Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 *Audio Decoder : AC3 (DD), MPEG	*Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 *Audio Decoder : AC3 (DD), MPEG	*Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 *Audio Decoder : AC3 (DD), MPEG
		IO Ports	USB 2.0	USB 2.0	USB 2.0
	Operating System		Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)
Certification	Safety		60950-1	60950-1	60950-1
	EMC		Class B(TBD)	Class B	Class B
	Environment		ENERGY STAR 8.0, Epeat	ENERGY STAR 8.0, Epeat	ENERGY STAR 8.0, Epeat
	Security		802.1x(WPA2 Enterprise)	802.1x(WPA2 Enterprise)	802.1x(WPA2 Enterprise)
	Included		: EAP-TLS, EAP-TTLS, EAP-PEAP Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries	: EAP-TLS, EAP-TTLS, EAP-PEAP Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries	: EAP-TLS, EAP-TTLS, EAP-PEAP Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries
	Stand		STN-L3240E	STN-L4355F	STN-L4355F
Accessories		Mount	WMN4070SE (Land Only)	WMN4070SE (Land Only)	WMN4070SE (Land Only)
Accessories		- IVUIN	WAAN IZE ON AE	WMN750ME	WMN750ME
Accessories	Optional		WMN750ME		
Accessories	Optional	Specialty Media Player	CML400XK N/A	CML400XK N/A	CML400XK N/A

Specifications

Model			QM55R-A	QM65R-A	QM75R-A
	Diagonal Size	Class	55	65	75
	Diagonal Size	Measured	54.6	64.5	74.5
	Туре		Edge LED BLU	Edge LED BLU	Edge LED BLU
	Resolution		UHD (3840 x 2160)	UHD (3840 x 2160)	UHD (3840 x 2160)
	Pixel Pitch (mm)		0.315(H) x 0.315(V)	0.372(H) x 0.372(V)	0.42975(H) x 0.42975(V)
	Active Display Area		1209.6(H) x 680.4(V)	1428.48 (H) x 803.52 (V)	1650.24 (H) x 928.26 (V)
	Brightness(Typ.)		500	500	500
Panel	Contrast Ratio (Typ.)		4000:1	4000:1	4000:1
	Viewing Angle(H/V)		178/178	178/178	178/178
	Response Time (G to	G)	8ms(Typ.)	8ms(Typ.)	8ms(Typ.)
			16.7M(True Display)	16.7M(True Display)	16.7M(True Display)
	Display Colors		1.07B(Ditherd10bit)	1.07B(Ditherd10bit)	1.07B(Ditherd10bit)
	Color Gamut Operation Hour		92% (DCI-P3, CIE1976)	92% (DCI-P3, CIE 1976)	92% (DCI-P3, CIE1976)
			24/7	24/7	24/7
	Haze		25%	25%	44%
Display	Dynamic C/R		MEGA	MEGA	MEGA
	H-Scanning Frequency		30 ~ 81kHZ	30 ~ 81kHZ	30 ~ 81kHZ
	V-Scanning Frequency		48~75HZ	48~75HZ	48~75HZ
	Maximum Pixel Frequ	Jency	594MHz	594MHz	594MHz
Sound	Speaker Type		Built in Speaker(10W + 10W)	Built in Speaker(10W+10W)	Built in Speaker(10W +10W)
		RGB	Display Port 1.2 (1)	Display Port 1.2 (1)	Display Port 1.2 (1)
		VIDEO	HDMI 2.0 (2)	HDMI 2.0 (2)	HDMI 2.0 (2)
	INPUT	HDCP	HDCP2.2	HDCP2.2	HDCP2.2
		AUDIO	Stereo Mini Jack, HDMI/Audio(Common)	Stereo Mini Jack, HDMI/Audio(Common)	Stereo Mini Jack, HDMI/Audio(Common)
		USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2
		RGB	N/A	N/A	N/A
Connectivity		VIDEO	N/A	N/A	N/A
	OUTPUT	AUDIO	Stereo mini Jack	Stereo mini Jack	Stereo mini Jack
	001101	PowerOut	N/A	N/A	N/A
		USB	N/A N/A	N/A N/A	N/A N/A
	EXTERNAL CONTROL		N/A RS232C(in/out) thru stereo jack, RJ45	N/A RS232C(in/out) thru stereo jack, RJ45	N/A RS232C(in/out) thru stereo jack, RJ45
	EXTERNAL CONTROL EXTERNAL SENSOR		RS232C(in/out) thru stereo jack, RJ45 IR	RS252C(in/out) thru stereo jack, RJ45 IR	RSZ5ZC(in/out) thru stereo jack, RJ45 IR
	Tuner		N/A	N/A	N/A
	Туре		Internal	Internal	Internal
	Power Supply	1	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz	AC100 - 240 V, 50/60 Hz
		Max[W/h]	143	181.5	231
Power		Typical[W/h]	108	131	178
	Power Consumption	Rating[W/h]	130	165	210
		BTU(Max)	487.6	618.9	787.7
		Sleep mode	0.5	0.5	0.5
		Off mode	N/A	N/A	N/A
	Dimension(mm)	Set	1235.1 x 707.9 x 46.3	1453.9 x 831.0 x 46.3	1681.1 x 960.1 x 49.7
	Dimension(mm)	Package	1402 x 858 x 163	1611 x 973 x 185	1871 x 1127 x 223
	Weight (kg)	Set	18.1	24.9	38.3
Mechanical	weight (kg)	Package	23.6	33.3	49
Spec	VESA Mount		200 X 200	400 X 400	400 X 400
	Protection Glass		N/A	N/A	N/A
	Stand Type		Foot Stand (Optional)	No	No
	Bezel Width (Top/Side/Bot) (mm)		9.2mm(U/L/R),11.2mm(B)	9.2mm(U/L/R), 11.2mm(B)	11.5mm(U/L/R),12.5mm(B)
Operation	Operating Temperatu	ıre	0°C~ 40°C	0°C~ 40°C	0°C~ 40°C
Operation	Humidity		10~80%	10~80%	10~80%
	Key		UHD Signage Display Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0	UHD Signage Display Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0	UHD Signage Display Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0
	Orientation		Landscape / Portrait	Landscape / Portrait	Landscape / Portrait
	Special	H/W	Temperature Sensor,Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker(10W 2ch), IP5x Rating, Wi-Fi/BT	Temperature Sensor,Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker(10W 2ch), IP5x Rating, Wi-Fi/BT	Temperature Sensor,Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker(10W 2ch), IP5x Rating, Wi-Fi/BT
		S/W	Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)	Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)	Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)
		Processor	Cortex A721.7GHz Quad-Core CPU	Cortex A721.7GHz Quad-Core CPU	Cortex A721.7GHz Quad-Core CPU
		On-Chip Cache	L1 Instruction Cache : 48KB L1 Data Cache : 32KB	L1 Instruction Cache : 48KB L1 Data Cache : 32KB	L1 Instruction Cache : 48KB L1 Data Cache : 32KB
Feature		Memory	L2 Cache : 2MB	L2 Cache : 2MB	L2 Cache : 2MB
		Clock Speed	1.7GHz	1.7GHz	1.7GHz
	Internal Player (Embedded H/W)	Main Memory	2.5GB	2.5GB	2.5GB
		Interface	LPDDR41.5GHz 64bit Graphic resolution : 1920x1080	LPDDR41.5GHz 64bit Graphic resolution : 1920x1080	LPDDR41.5GHz 64bit Graphic resolution : 1920x1080
		Graphics	Output resolution : 3840x2160 (Scale up from graphic processing result.)	Output resolution : 3840x2160 (Scale up from graphic processing result.)	Output resolution : 3840x2160 (Scale up from graphic processing result.)
		Storage (FDM)		8GB (3.88GB Occupied by O/S, 4.12GB Available) *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC,	
		Multimedia IO Ports	VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 *Audio Decoder : AC3 (DD), MPEG USB 2.0	VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 *Audio Decoder : AC3 (DD), MPEG USB 2.0	VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 *Audio Decoder : AC3 (DD), MPEG USB 2.0
	Operating System		Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)	Tizen 4.0 (VDLinux)
	Safety		60950-1	60950-1	60950-1
Certification	EMC		Class B	Class B	Class B
	Environment		ENERGY STAR 8.0, Epeat	ENERGY STAR 8.0, Epeat	ENERGY STAR 8.0, Epeat
			802.1x(WPA2 Enterprise)	802.1x(WPA2 Enterprise)	802.1x(WPA2 Enterprise)
Accessories	Security		: EAP-TLS, EAP-TTLS, EAP-PEAP Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries	: EAP-TLS, EAP-TTLS, EAP-PEAP Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries	: EAP-TLS, EAP-TTLS, EAP-PEAP Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries
	Stand		STN-L4355F	No	No
	Optional	Mount	WMN4070SE (Land Only)	WMN4277SE (Land Only)	WMN4277SE (Land Only)
			WMN750ME CML400XK	WMN750ME	WMN6575SE CLM450K
		Specialty Media Player	CML4UUXK N/A	CLM450K N/A	CLM450K N/A
		A colo Flayel	N/A	11/74	11/2

About Samsung Electronics Co., Ltd.

Samsung Electronics Co., Ltd. inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, cameras, digital appliances, medical equipment, network systems, and semiconductor and LED solutions. For the latest news, please visit the Samsung Newsroom at news.samsung.com.

Smart Signage

For more information about Samsung Smart Signage QMR-A series Displays, visit www.samsung.com/business or www.samsung.com/displaysolutions

Copyright © 2021 Samsung Electronics Co. Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co. Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd. 416, Maetan 3-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 443-772, Korea

2021-06

